

SCK0YTL40-2.92 Y Type Calibration Kit

(0.1 - 40GHz / 2.92mm)

Model						
SCK0YTL40-2.92						
Type						
2.92mm						
	$C_0 (F*10^{-15})$	$C_1 (F*10^{-27}/Hz)$	$C_2 (F*10^{-36}/Hz^2)$	$C_3 (F*10^{-45}/Hz^3)$	DELAY (ps)	LOSS (GΩ/s)
Open (m)	37.0883	70.7568	1.03487	0.077080	23.6831	4.93052
Open (f)	36.842	164.764	-9.2586	0.294455	23.6831	3.79386
	$L_0 (H*10^{-12})$	$L_1 (H*10^{-24}/Hz)$	$L_2 (H*10^{-33}/Hz^2)$	$L_3 (H*10^{-42}/Hz^3)$	DELAY (ps)	LOSS (GΩ/s)
Short (m)	13.9373	-2300.69	97.9591	-1.29741	26.4683	3.62125
Short (f)	5.91213	-1298.99	61.0329	-0.855233	26.4683	4.15172

Through	
Electrical Delay (ps)	127.8
Offset Loss (GΩ/s)	3.60

No.367, Fuxing N. Rd.,105 Taipei,Taiwan Tel: +886. 909 602 109

sales@salukitec.com www.salukitec.com

