

# SCKCL67A2-1.85 High Precision Calibration Kit

(DC - 67GHz / 1.85mm)

## Key Features

- The 1.85mm Coaxial port
- Broadband: DC~67GHz
- High-performance
- Multi-short-circuit form, fixed load calibration



## Overview

Saluki SCKCL67A2-1.85 mechanical calibration kit is an economical calibration piece with an operating frequency of up to 67GHz and is mainly used to calibrate a vector network analyzer with 1.85mm ports.

Note 1: The technical specifications of DC-10MHz are based on 10MHz and are not tested separately.

Note 2: The phase offset of the openers and shorters represents the phase offset relative to the standard parts

2. Environmental adaptability

Operating temperature:  $23^{\circ}\text{C} \pm 3^{\circ}\text{C}$

Storage temperature:  $-20^{\circ}\text{C}$  to  $+70^{\circ}\text{C}$

## Technical Specifications Below:

# SCKCL67A2-1.85 High Precision Calibration Kit

(DC - 67GHz / 1.85mm)

Model	Frequency	Type	Spec.	List	Qty.
SCKCL67A2- 1.85 (Calibration Level)	DC -67GHz	Load: VSMR	$\geq 30\text{dB}$ (DC-26.5GHz) $\geq 28\text{dB}$ (26.5GHz-50GHz) $\geq 25\text{dB}$ (50GHz-67GHz)	Short:1.85mm(M)	1
		Adaptor: VSMR	$\geq 33\text{dB}$ (DC-4GHz) $\geq 24\text{dB}$ (4GHz-26.5GHz) $\geq 22\text{dB}$ (26.5GHz-50GHz) $\geq 20\text{dB}$ (50GHz-67GHz)	Short:1.85mm(F)	1
		Open	$\pm 3^\circ$ (DC-67GHz)	Open:1.85mm(M)	1
				Open:1.85mm(F)	1
		Short	$\pm 2.5^\circ$ (DC-67GHz)	Load:1.85mm(M)	1
				Load:1.85mm(F)	1
				1.85mm JJ adaptor	1
				1.85mm JK adaptor	1
				1.85mm KK adaptor	1
				Torque spanner	1
3.5mm Torque spanner	Torque 90 N.cm $\pm$ 2.7 N.cm				

*Note: Information will conduct the necessary updates , the contents of this document are subject to change without notice*