

STB8822 Series Handheld LCR Meter

Features

- 0.1% high test accuracy
- Maximum test signal frequency : 100kHz
- Selectable test signal level
- With DCR function
- Enhanced protection capability of input terminal impact
- 40000 counts for primary parameter, D/Q resolution 0.0001
- Typical ultra-low consumption: 25mA
- Innovatively compatible terminal configuration: 5-terminal test slot and 3-terminal rubber jack
- Intellectualized auto LCR function
- AC test speed up to 4 meas/sec (DCR: 3 meas/sec), fast automatic range switch design
- Constant 100Ω output impedance
- Percentage display and 4-tolerance comparator: 1/5/10/20%
- Battery charge in startup & shutdown
- Test terminal protection function
- Data-hold, Max./Min./Average value recording
- Real-time function configuration selection and working condition hold capacity
- Standard configuration Mini-USB communication interface and SCPI command set
- Free FastAccess PC communication software on our website
- Gorgeous dual-color cast shell



STB8822 series
Dimension: 90(W) x 190(H) x 40(D)
Weight: 350g

Brief Introduction

■ With its advanced impedance test technology, Saluki Tech has launched STB8822 series handheld LCR meters. This series currently possess the most powerful functions and outstanding performance in this industry comparable with bench LCR meters. Meanwhile it is the achievement of Saluki in the passive-component testing field.

STB8822 series apply the ultra-low power consumption design and high density SMD assembly techniques and can simultaneously display primary and secondary parameters on a LCD display with backlight. The dual-color shell is gorgeously once shaped; and functions are easy to operate. The test frequency is up to 100 kHz, the readings of primary parameter 40,000 counts and the resolution of dissipation factor 0.0,001. Accurate and convenient measurements of passive-components can be achieved in different occasions for a long time. In order to meet different market demand, multiple signal level and DCR test function are increased on STB8822D/E. The test accuracy can reach 0.1%. With USB interface, STB8822 series can conveniently communicate with a PC and be remotely controlled by a PC. In order to satisfy the increasing test requirements for SMD and balance the different needs for performance and price, two types of 4-terminal Kelvin test tweezers: SBF0009C and SBF0029C are optional for users' choice.

Specifications

Model	STB8822A		STB8822C	STB8822D	STB8822E
Function					
Test Parameter	Primary parameters: L / C / R / Z Secondary parameters: D / Q / R /θ/ ESR			Primary parameters: L / C / R / Z/ DCR Secondary parameters: D / Q / R /θ/ ESR	
Equivalent Circuit	Series and Parallel				
Parameter and Equivalent Mode	Hold, Auto				
Ranging Mode	Auto				
Measurement Terminals	3-terminal, 5-terminal				
Measuring Speed	4meas/sec, 1.5meas/sec				
DCR Measuring Speed	-----			3meas/sec	
Calibration Function	Open, short				
Comparator Function	1%, 5%, 10%, 20%			1%, 5%, 10%, 20%	
Input fuse	0.1A / 250V				
Interface	Mini-USB (virtual serial port)				
Test signal					
Test Frequency	100Hz, 120Hz, 1kHz, 10kHz,	100Hz, 120Hz, 1kHz, 10kHz, 100kHz	100Hz, 120Hz, 1kHz, 10kHz,	100Hz, 120Hz, 1kHz, 10kHz, 100kHz	
Test Level	0.6Vrms			0.3 Vrms, 0.6 Vrms, 1 Vrms	
Output Resistance	100Ω				
Display					
Display	LCD Primary-Secondary dual display, with backlight (STB8822 not available)				
Reading	Max. Primary parameters: 40,000 digits, secondary parameters D/Q Minimum resolution: 0.0001				
Basic accuracy	0.25%			0.1%	
Measuring Range					
L	0.00μH - 1000.0H		0.000μH - 1000.0H	0.00μH - 1000.0H	0.000μH - 1000.0H
C	0.00pF - 20.000mF		0.000pF - 20.000mF	0.00pF - 20.000mF	0.000pF - 20.000mF
Z/R	0.0000Ω- 10.000MΩ				
DCR	-----	-----	0.0000Ω- 20.000MΩ		
ESR	0.0000Ω- 999.9Ω				
D	0.0000 - 9.999				
Q	0.0000 - 9999				
θ	0.00°- ±180.0°				
Power Requirements					
Battery model	STB8822 / A : IEC 6LR61, 9V alkaline battery STB8822C/D/E : LH-200H7C,8.4V Ni-MH 200mAH rechargeable				
AC power adapter	battery Input: 220V/50Hz, Output: 12V-15V (100Ω Load)				
Standby Currant	Max.2μA		18μA	11μA	
Battery life	16 hours (typical) , new alkaline battery, with backlight off				
Auto power off	5min, 15min, 30min, 60min, OFF available; Factory Default : 5min				
Low voltage indicator	When battery voltage drops below 6.8V, low voltage indicator turns on.				

Standard Accessories

MINI USB Communication cable
 SBF0028 AC power adapter
 SBF0004F Two-terminal Test Cable
 SBF0010B Gilded shorting plate

SBF0027AS 4 terminal Kelvin test cable
 SBF0029C SMD Kelvin test cable(not included in SH2822/A)
 8.4V Rechargeable battery(not included in SH2822/A)
 Alkaline battery (only for SH2822/A)