

STB8829X Series Precision LCR Meter

Features

- 800×RGB×480 7-inch TFT LCD display
- Basic accuracy: 0.05%
- Test signal frequency of 1MHz, resolution of 1mHz, 5-digit frequency input
- Strongest signal source selection:
 10V/100mA programmable AC test level
 10V/100mA programmable DC bias supply
 10V/50mA standalone DC voltage source
 1A/2A interior DC bias current source (optional)
 120A external bias source (optional)
- Maximum test speed: 9ms/time
- Simultaneous display of 4 kinds of test parameters
- 201-point list sweep function
- Continuous curve scanning/graphical analysis function
- Internal storage of 100 sets of LCRZ setting files and 10 sets of GIF image
- GIF image and CSV data files can be saved to USB storage directly
- HANDLER, USB, LAN, RS232C, GPIB (option), DCI interface



RS232	USB HOST	USB DEVICE	HANDER	LAN	GPIB
standard	standard	standard	standard	standard	option

STB8829A/STB8829C

Dimension (mm): 400(W) x 132(H) x385(D)
Net weight : 13kg

Applications

Passive component:

Impedance parameter estimation and performance analysis of capacitor, inductor, magnetic core, resistor, piezoelectric devices, transformers, chip components and network components

Semiconductor component

Parasitic parameter test and analysis of LED driver integrated circuit
C-VDC features of varactors

Parasitic parameter analysis of transistors or integrated circuit

Other components

Impedance assessment of printed circuit boards, relays, switches, cables, batteries

Dielectric material

Dielectric constant and loss angle evaluation of plastics, ceramics and other materials

Magnetic materials

Magnetic permeability and loss angle assessment of ferrite, amorphous body and other magnetic materials

Semiconductor materials

Dielectric constant, electrical conductivity and C-V characteristics of semiconductor materials

Liquid crystal cell

Dielectric constant, elastic constant and C-V characteristics of liquid crystal cell

Specifications

Display	800×RGB×480 7-inch TFT LCD display	
Frequency of test signal	STB8829A	20Hz—300kHz
	STB8829C	20Hz—1MHz
	Minimum resolution	1mHz, 5-digit frequency input
	Accuracy	0.01%
AC Level	Voltage range of test signal	5mV—10Vrms
	Minimum resolution of voltage	100µV, 3-digit input
	Accuracy	10% x set voltage + 2mV
	ALC ON	6% x set voltage + 2mV
	ALC OFF	50µA—100mA
	Current range of test signal	1µA, 3-digit input
	Minimum resolution of current	10% x set current + 20µA
	Accuracy	6% x set voltage + 20µA
DC bias voltage source	Voltage/Current range	0V— ±10V / 0mA—±100mA
	Resolution	0.5mV / 5µA
	Voltage accuracy	1% x set voltage + 5mV
	ISO ON	Be used for the bias test of inductance and transformer
AC Source impedance	ISO ON	100Ω
	ISO OFF	30Ω, 50Ω, 100Ωselectable
DCR Source impedance		30Ω, 50Ω, 100Ωselectable
DC Independent voltage source	Voltage/current range	0V— ±10V / 0mA—±50mA
	Resolution	0.5mV / 5µA
	Voltage accuracy	1% x set voltage + 5mV
	Output resistance	100Ω
Test parameters of LCR		Z , Y , C, L, X, B, R, G, D, Q, θ, DCR, Vdc-Idc
Parameter display of test page		Two sets of main/sub parameters, the second set can be set as ON/OFF; There can be 10 pages of list sweep and 15 points per page at most; Multiple parameters continuous sweep graphical analysis.

Basic accuracy	LCR test parameter	0.05%
	Calibration	Warm-up time ≥ 30 seconds; Environment temperature: 23±5°C; Signal voltage: 0.3Vrms-1Vrms ; Zeroing: After OPEN or SHORT; Length of test cable: 0 m
Measurement time (≥10 kHz)	Fast: 9 ms / time ; Medium: 67 ms / time; Slow:187 ms / time Plus the refresh time of display character	
Display range of LCR parameter	Z ,R,X,DCR	0.00001Ω — 99.999MΩ
	Y ,G,B	0.00001μs — 99.999s
	C	0.00001pF — 9.9999F
	L	0.00001μH — 99.999kHz
	D	0.00001 — 9.9999
	Q	0.00001 — 9999.9
	θ(DEG)	-179.99° — 179.99°
	θ(RAD)	-3.14159 — 3.14159
	Δ%	-999.999% — 999.999%
	Equivalent circuit	Serial, Parallel
Range mode	Auto, Hold	
Trigger mode	Internal, Manual, External, Bus	
Average times	1-256	
Calibration function	Open, short calibration with full frequency or dot frequency, Load	
Math operation	Direct reading, ΔABS, %	
Delay time setup	0-999, minimum resolution: 100us	
Comparator	10-bin sorting, BIN1-BIN9, NG, AUX	
List sweep	Bin counter PASS/FAIL on front panel, LED indication <ul style="list-style-type: none"> ·201 -point list sweep function ·List sweep of frequency, AC voltage/current, internal/external DC bias voltage/current and independent DC source voltage can be performed on each page. Each sweep point can be sorted separately. 	
Graphical analysis	<ul style="list-style-type: none"> ·Graph scanning and analysis of frequency, AC level and DC bias can be performed. ·Set the sweep start point, end point and each sweep point. ·Display the maximum value, minimum value and read any of the chosen sweep point ·Scanning graphs can be stored into internal or external USB memory. 	
Internal nonvolatile memory	100 sets of LCRZ setting files memory, 201 times test results, 10 sets of GIF image, CSV data files	
External USB memory	<ul style="list-style-type: none"> ·GIF image, CSV data files ·LCRZ setting files memory ·Test data can be stored via USB memory directly. 	
Interface	1A bias current source	1A DC bias current source (optional) can be stalled
	I/O interface	HANDLER on rear panel
	SCI	USB, RS232C
	PCI	GPIB(optional)
	NI	LAN
Memory interface		USB HOST(front panel)
General Specifications		
Operating temperature and humidity		0°C – 40°C, ≤ 90%RH
Power supply	Voltage	99V – 121V, 198V – 242V AC
	Frequency	47Hz – 63Hz
Consumption		Max. 80 VA
Dimension(W×H×D)		400mm × 132mm × 385mm
Weight		Approx.13 kg

Standard Accessories

Three core power cord

SBF0010 Gold-plated short circuit board

SBF0011AS 4 terminal pair Kelvin test clip leads(only STB8829A)

SBF0011BS 4 terminal pair Kelvin test clip leads(only STB8829C)

SBF0048 Four-terminal test fixture