



1466 Series

Signal Generator

1466C/D/E/G/H/L/N/P

(6kHz to 13GHz/20GHz/33GHz/45GHz/53GHz/67GHz/90GHz/110GHz)



Ceyear Technologies Co., Ltd

Product Overview

Ceyear 1466 series signal generator is a general-purpose test instrument for microwave and millimeter-wave cutting-edge testing, with wide frequency coverage, high signal spectral purity, output power with high accuracy and large dynamic range. With single-machine dual-RF channel and design, can meet your various test requirements. Rich built-in functions such as analog scanning, analog modulation and pulse modulation make daily testing more convenient.

The new upgrade of human-computer interaction, with large screen touch graphics guided interaction, mobile browser access control, multi-manufacturer power meter connection identification, multi-client deployment, SCPI command recording, control interface customization and a series of new functions to bring user's test happiness. The Ceyear 1466 series signal generator is ideal for high standard testing from component level to system level.



Main Features

Excellent RF Performance

- **Coaxial connectors:** 6kHz to 13GHz/20GHz/33GHz/45GHz/53GHz/67GHz/90GHz/110GHz
- **Excellent spectral purity:** SSB < -132 dBc/Hz (typ.10 GHz carrier at 10kHz offset), Spurious < -80 dBc (10 GHz carrier)
- **Brilliant wideband noise floor,** SSB< -161 dBc/Hz (typ.20GHz carrier at 30MHz offset)
- **Large dynamic range of high output power:** settable power ranges from -150dBm to +25dBm
- **Support AM,FM, Φ M and pulse modulation,** the min.pulse width of pulse modulation is 20ns
- **Support stepping, list, power and analog scanning**
- **Support one main unit with two channels,** each channel can be set separately

Newly updated interactive interface

- Large-screen touch graphics guide interaction, support user-defined menus
- Cross-platform client and browser access control
- SCPI instruction real-time recording and program control sample project automatic generation


Excellent RF Performance

110GHz coaxial frequency coverage, easier and more accurate testing



Ceyear 1466 series signal generator coaxial output frequency covers 6kHz to 110GHz, at the same time, it has high-precision large dynamic range amplitude control which can provide excellent power accuracy and stability. Ceyear 1466 series signal generator supports external Ceyear 8240X series signal source extender which can further expand the frequency to 750GHz. It is a powerful tool for efficient millimeter-wave 5G communication RF conformance testing .

Excellent spectral purity, making cutting-edge testing easier

Ceyear 1466 series signal generator supports high spectral purity output signal, SSB phase noise: -145dBc/Hz @10kHz offset at 1GHz carrier, -132dBc/Hz @10kHz offset at 10GHz carrier, Wideband noise floor: -161dBc/Hz @30MHz offset at 20GHz carrier, spurious<-80dBc at 10GHz carrier, harmonics <-55dBc. The purer signal makes you no longer troubled by interfering signals when testing microwave and millimeter wave components, systems, and OTA.




Option H04-2: SSB phase noise measured value


**1466D harmonic measured value****1466G harmonic measured value**

Large dynamic range, high accuracy power output

Ceyear 1466 series signal generator maximum output power typical value: +27dBm @5GHz, +24dBm@ 20GHz, +25dBm @30GHz, +22dBm@ 60GHz, +3dBm @110GHz. Minimum settable output power can up to -150dBm,dynamic range of output power can reach 170dB. Industry-leading power accuracy specifications:<0.5dB below 20GHz(typ).



1466D max. output power measured value (large power option H05-20)



1466G max. output power measured value (large power option H05-45)


Rich built-in functions


Full range of analog modulation

Amplitude modulation, frequency modulation, phase modulation and pulse modulation are supported. It has complex pulse modulation functions such as double pulse, pulse train, PRF jittering, PRF staggering, and PRF sliding.

**Analog modulation interface****Multi-style sweep mode**

Support Step sweep, List sweep, ramp sweep and power sweep functions.

**Step scanning measured value**




Analog scanning (slope scanning) measured value

Newly upgraded human-machine interaction

Touchable graphic guide interaction

The 11.6-inch high-resolution touch screen is used to clearly display the main parameters and instrument status information, and with the signal flow diagram guidance interface, the display is more intuitive and the interaction is more friendly.



Signal flow diagram guidance interface

Flexible user control interface


Support user-defined menus, tailor-made personalized user control interface according to test habits, realize multi-function operations in one window, and avoid the trouble of too deep menus and repeated searches.



User-defined menu

Support cross-platform client control

Cross-platform client and browser access control. Support multiple clients to connect at the same time, and the working status of the instrument is refreshed synchronously. Supports web browser access control for mobile devices.



Browser access

Simultaneous recording of SCPI commands and one-click script generation

Not only can you export recorded SCPI commands with one click, but also automatically generate VS (C++, C#), Qt, Matlab, LabView program control example projects, making program control easier.



SCPI command recording

Technical Specifications

Frequency characteristics					
Frequency	1466C:6kHz to 13GHz 1466D:6kHz to 20GHz 1466E:6kHz to 33GHz 1466G:6kHz to 45GHz 1466H:6kHz to 53GHz 1466L:6kHz to 67GHz 1466N:6kHz to 90GHz 1466P:6kHz to 110GHz	Frequency range	N1		
		6kHz≤f≤10MHz	-		
		10MHz<f≤50MHz	-		
		50MHz<f≤62.5MHz	1/256		
		62.5MHz<f≤125MHz	1/128		
		125MHz<f≤250MHz	1/64		
		250MHz<f≤500MHz	1/32		
		500MHz<f≤1GHz	1/16		
		1GHz<f≤2GHz	1/8		
		2GHz<f≤4GHz	1/4		
		4GHz<f≤8GHz	1/2		
		8GHz<f≤20GHz	1		
		20GHz<f≤40GHz	2		
		40GHz<f≤67GHz	4		
		100GHz<f≤110GHz	6		
Resolution	0.001Hz				
Switching speed	<15ms				
Aging rate(typ)	±5×10 ⁻¹⁰ /day after 30 days				
Reference output	Frequency	10MHz			
	Power	>+4dBm into 50Ω load			
Reference input	Frequency	1 to 100MHz,step:1Hz			
	Power	-5dBm to +10dBm,impedance: 50Ω			
Sweep characteristics					
Sweep mode	Step sweep List sweep Ramp(analog) sweep (option S15), Power sweep(option S16)				
Ramp(analog) sweep (Option S15)	Maximum sweep rate	f>4GHz	400MHz/ms		
	Frequency accuracy	±0.05% of span (at 100ms sweep time, for sweep spans less than maximum values as 100ms)			
Power characteristics					
Minimum output power	Model	Standard	Option H01-90/120/130		
	1466C/D/E/G	-10dBm(can be set as -20dBm)	Option H01-130: 6kHz≤f≤100kHz -90.0dBm(minimum power:-150dBm) f > 100kHz -120.0dBm(minimum power:-150dBm) settable output		
	1466H/L	-10dBm(can be set as -20dBm)	Option H01-90: -90.0dBm(minimum power:-110dBm) settable output Option H01-120: -90.0dBm(minimum power:-150dBm) settable output		

			poer:-140dBm)	
	1466N/P	-10dBm(can be set as -20dBm)	Option H01-50: -50.0dBm(minimum poer:-70dBm)	settable output
1466C				
	Configuration			
	Frequency range	Standard	Programmable step attenuator Option H01-130/B130	High output power (option H05-13/B13)
	6kHz≤f≤50MHz	≥+15.0	≥+15.0	≥+15.0
	50MHz<f≤13GHz	≥+15.0	≥+15.0	≥+20.0
1466D				
	Configuration			
	Frequency range	Standard	Programmable step attenuator Option H01-130/B130	High output power and programmable step attenuator (option H01-130+H05-13; H01-B130+H05-B13)
	6kHz≤f≤50MHz	≥+15.0	≥+15.0	≥+15.0
	50MHz<f≤20GHz	≥+15.0	≥+15.0	≥+20.0
1466E				
	Configuration			
	Frequency range	Standard	Programmable step attenuator Option H01-130/B130	High output power and programmable step attenuator (option H01-130+H05-33; H01-B130+H05-B33)
	6kHz≤f≤50MHz	≥+8.0	≥+8.0	≥+8.0
	50MHz<f≤6GHz	≥+12.0	≥+12.0	≥+20.0
	6GHz<f≤18GHz	≥+12.0	≥+12.0	≥+18.0
	18GHz<f≤30GHz	≥+12.0	≥+12.0	≥+17.0
	30GHz<f≤33GHz	≥+12.0	≥+12.0	≥+18.0
1466G				
	Configuration			
	Frequency range	Standard	Programmable step attenuator Option H01-130/B130	High output power and programmable step attenuator (option H01-130+H05-45; H01-B130+H05-B45)
	6kHz≤f≤50MHz	≥+8.0	≥+8.0	≥+8.0
	50MHz<f≤6GHz	≥+12.0	≥+12.0	≥+20.0
	6GHz<f≤18GHz	≥+12.0	≥+12.0	≥+18.0
	18GHz<f≤30GHz	≥+12.0	≥+12.0	≥+17.0
	30GHz<f≤40GHz	≥+12.0	≥+12.0	≥+18.0
	40GHz<f≤45GHz	≥+12.0	≥+12.0	≥+14.0

1466H					
Frequency range	Configuration	Standard	Programmable step attenuator Option H01-90/120, H01-B90/120	High output power (option H05-45/B53)	High output power and programmable step attenuator (option H01-90/120+H05-53; H01-B90/120+H05-B53)
6kHz≤f≤50MHz	≥+8.0	≥+8.0	≥+8.0	≥+8.0	≥+8.0
50MHz<f≤20GHz	≥+8.0	≥+8.0	≥+17.0	≥+16.0	≥+16.0
20GHz<f≤40GHz	≥+8.0	≥+8.0	≥+15.0	≥+13.0	≥+13.0
40GHz<f≤53GHz	≥+8.0	≥+8.0	≥+20.0	≥+18.0	≥+18.0
1466L					
Frequency range	Configuration	Standard	Programmable step attenuator Option H01-90/120, H01-B90/120	High output power (option H05-67/B67)	High output power and programmable step attenuator (option H01-90/120+H05-53; H01-B90/120+H05-B53)
6kHz≤f≤50MHz	≥+8.0	≥+8.0	≥+8.0	≥+8.0	≥+8.0
50MHz<f≤20GHz	≥+8.0	≥+8.0	≥+17.0	≥+16.0	≥+16.0
20GHz<f≤40GHz	≥+8.0	≥+8.0	≥+15.0	≥+13.0	≥+13.0
40GHz<f≤53GHz	≥+8.0	≥+8.0	≥+20.0	≥+18.0	≥+18.0
53GHz<f≤65GHz	≥+8.0	≥+8.0	≥+18.0	≥+16.0	≥+16.0
65GHz<f≤67GHz	≥+8.0	≥+8.0	≥+15.0	≥+12.0	≥+12.0
1466N					
Frequency range	Configuration	Standard	Programmable step attenuator Option H01-50/B50,	High output power (option H05-90/B90)	High output power and programmable step attenuator (option H01-50+H05-90; H01-B50+H05-B90)
6kHz≤f≤50MHz	≥+5.0	≥+5.0	≥+8.0	≥+8.0	≥+8.0
50MHz<f≤20GHz	≥+5.0	≥+5.0	≥+13.0	≥+13.0	≥+13.0
20GHz<f≤40GHz	≥+5.0	≥+5.0	≥+12.0	≥+10.0	≥+10.0
40GHz<f≤67GHz	≥3.0	≥+3.0	≥+10.0	≥+8.0	≥+8.0
67GHz<f≤85GHz	≥0.0	≥0.0	≥+7.0	≥+5.0	≥+5.0
85GHz<f≤90GHz	≥-5.0	≥-5.0	≥3.0	≥0.0	≥0.0
1466P					
Frequency range	Configuration	Standard	Programmable step attenuator Option H01-50/B50,	High output power (option H05-90/B90)	High output power and programmable step attenuator (option H01-50+H05-90; H01-B50+H05-B90)
6kHz≤f≤50MHz	≥+5.0	≥+5.0	≥+8.0	≥+8.0	≥+8.0
50MHz<f≤20GHz	≥+5.0	≥+5.0	≥+13.0	≥+13.0	≥+13.0
20GHz<f≤40GHz	≥+5.0	≥+5.0	≥+12.0	≥+10.0	≥+10.0

	40GHz<f≤67GHz	≥3.0	≥3.0	≥+10.0	≥+8.0	
	67GHz<f≤85GHz	≥0.0	≥0.0	≥+7.0	≥+0.0	
	85GHz<f≤110GHz	≥-5.0	≥-5.0	≥+3.0	≥+5.0	
Power accuracy (25±10°C)						
Standard						
	Frequency	Power(dBm)	-10dBm<P≤+10dBm	+10dBm<P≤+25dBm	+25dBm<P	
	6kHz≤f≤50MHz		±1.0dB	±1.0dB	—	
	50MHz<f≤3GHz		±0.5dB	±0.5dB	±1.0dB	
	3GHz<f≤20GHz		±0.9dB	±0.9dB	±1.2dB	
	20GHz<f≤40GHz		±1.0dB	±1.0dB	—	
	40GHz<f≤50GHz		±1.3dB	±1.3dB	—	
	50GHz<f≤67GHz		±1.8dB	±1.8dB	—	
	67GHz<f≤85GHz		±2.0dB	±2.0dB	—	
	85GHz<f≤110GHz		±2.2dB	—	—	
H01-130/120/90/50/B130 programmable step attenuator option						
	Frequency	Power(dBm)	+120dBm<P≤-90dBm	-90dBm<P≤-50dBm	-50dBm<P≤+10dBm	
	6kHz≤f≤50MHz		—	±1.5dB	±1.0dB	
	50MHz<f≤3GHz		±1.2dB	±0.7dB	±0.5dB	
	3GHz<f≤20GHz		±1.8dB	±0.9dB	±0.9dB	
	20GHz<f≤40GHz		—	±1.2dB	±1.0dB	
	40GHz<f≤50GHz		—	±1.5dB	±1.3dB	
	50GHz<f≤67GHz		—	±2.0dB	±1.8dB	
	67GHz<f≤85GHz		—	±2.0dB	±2.0dB	
	85GHz<f≤110GHz		—	±2.2dB	—	
Power resolution	0.01dB					
Temperature stability	0.02dB/°C (typ)					
Output impedance	50Ω(nom)					
VSWR(internal leveled)(typ)	100kHz≤f≤20GHz		<1.6			
	20GHz<f≤40GHz		<1.8			
	40GHz<f≤67GHz		<2.0			
	67GHz<f≤85GHz		<2.5			
	85GHz<f≤110GHz		<3.0			
Maximum reverse power	0.5W(0V DC)(nom)					
Spectral purity characteristics						
Harmonics (dBc at +10dBm or maximum specified output power, whichever is lower)	Frequency		Standard			
	100kHz≤f≤3GHz		<-30dBc			
	3GHz<f≤67GHz		<-55dBc			
	67GHz<f≤110GHz		<-40dBc			
Sub-harmonics (at +10dBm or maximum specified output power, whichever is lower)	6kHz≤f≤20GHz		<-80dBc			
	20GHz<f≤40GHz		<-60dBc			
	40GHz<f≤110GHz		<-50dBc			
Non-harmonics(dBc at 0dBm, for offset >3kHz)	Frequency		Option H04-1		Option H04-2	
	6kHz≤f≤250MHz		<-58dBc		<-68dBc	
	250MHz<f≤4GHz		<-70dBc		<-80dBc	

	4GHz<f≤10GHz	<-70dBc			<-80dBc			
	10GHz<f≤20GHz	<-64dBc			<-74dBc			
	20GHz<f≤40GHz	<-58dBc			<-68dBc			
	40GHz<f≤67GHz	<-52dBc			<-62dBc			
	67GHz<f≤110GHz	<-48dBc			<-58dBc			
SSB phase noise (dBc/Hz, at +10dBm or maximum specified output power, whichever is lower)	Offset from carrier	10Hz	100Hz	1kHz	10kHz	100kHz	1MHz	10MHz
	H04-1 low phase noise option							
	100MHz	—	<-118	<-141	<-148	<-150	—	—
	250MHz<f≤500MHz	—	<-111	<-130	<-145	<-143	—	—
	0.5 GHz<f≤1GHz	—	<-105	<-124	<-140	<-138	—	—
	1 GHz<f≤2GHz	—	<-100	<-118	<-134	<-132	—	—
	2 GHz<f≤4GHz	—	<-93	<-113	<-128	<-126	—	—
	4GHz<f≤10GHz	—	<-85	<-105	<-120	<-118	—	—
	10GHz<f≤20GHz	—	<-79	<-99	<-114	<-112	—	—
	20GHz<f≤40GHz	—	<-73	<-93	<-108	<-106	—	—
	40GHz<f≤67GHz	—	<-67	<-87	<-103	<-101	—	—
	67GHz<f≤110GHz	—	<-61	<-81	<-97	<-95	—	—
	H04-2 ultra low phase noise option							
	100MHz	<-102	<-118	<-141	<-148	<-150	<-152	<-152
	250MHz<f≤500MHz	<-92	<-112	<-135	<-146	<-148	<-150	<-150
	0.5GHz<f≤1GHz	<-90	<-110	<-134	<-144	<-147	<-150	<-150
	1GHz<f≤2GHz	<-88	<-104	<-127	<-138	<-142	<-148	<-148
	2 GHz<f≤4GHz	<-82	<-99	<-122	<-135	<-136	<-146	<-148
	4GHz<f≤10GHz	<-77	<-91	<-115	<-128	<-128	<-140	<-154
	10GHz<f≤20GHz	<-71	<-85	<-109	<-122	<-122	<-134	<-152
	20GHz<f≤40GHz	<-63	<-79	<-99	<-116	<-116	<-128	<-142
	40GHz<f≤67GHz	<-57	<-73	<-94	<-110	<-110	<-122	<-136
	67GHz<f≤110GHz	<-51	<-67	<-88	<-104	<-104	<-116	<-130
Modulation characteristics								
Frequency modulation (50MHz<f≤50GHz, Option S11)	Maximum deviation:N×20MHz(N: YO harmonic number) Accuracy(at 1kHz, N×20kHz≤deviation<N×800kHz): <± (2.5%× set frequency offset +20Hz) Modulation rate(3dB bandwidth, N×500kHz frequency offset):DC-10MHz Distortion(at 1kHz, N×20kHz≤deviation<N×800kHz): <1%							
Phase modulation (50MHz<f≤50GHz, Option S11)	Maximum deviation: Normal mode: N×20.0rad(N: YO harmonic number) Broadband mode: N×2rad Low noise mode: N×0.2rad Accuracy(at 1kHz,N×0.2rad≤phase deviations<N×8rad,normal mode): <± (3% of setting deviation+0.01 rad) Modulation rate (3dB bandwidth), (Broadband mode): DC to 10MHz(typ) Distortion (at 1kHz, N×0.8rad≤deviations<N×8rad, THD): <0.8%							

Amplitude modulation (10MHz<f≤50GHz, Option S11)	Maximum depth: >90% Modulation rate (3 dB bandwidth, 30% modulation depth): DC to 100kHz Accuracy (1kHz modulation rate, 30% modulation depth): ±(5% of setting+1%) Distortion (1kHz modulation rate, Linear mode, THD, 30% modulation depth) <1.5%		
Pulse modulation (option S13 would cover option S12)	Option S12	>50MHz to 67GHz	>67GHz
	On/off ratio	>80dB	>60dB
	Rise/fall times	<20ns	<30ns
	Repetition frequency	0Hz to 25MHz	0Hz to 25MHz
	Minimum pulse width	0.1μs	0.1μs
	Option S13	>50MHz to 67GHz	
	On/off ratio	>80dB	—
	Rise/fall times	<10ns	—
	Repetition frequency	0Hz to 25MHz	—
	Minimum pulse width	20ns	—
LF out/Function generator(option S14)	Support frequency/phase modulation, amplitude modulation output Waveform: sine, square, triangle, sawtooth, noise, double sine, sweep sine Frequency range: DC to 10MHz for sine, double sine, sweep sine waveform; 0.1Hz to 1MHz for square, triangle, sawtooth waveform. Frequency resolution: 0.1Hz Low frequency output: amplitude: 0 to 5Vpp(nom), into 50Ω load		
General characteristics			
RF output interface	1466C/D:3.5mm (Male), Impedance 50Ω 1466E/G:2.4mm (Male), Impedance 50Ω 1466H/L:1.85mm (Male), Impedance 50Ω 1466N/P:1.0mm (Male), Impedance 50Ω		
Dimension (W×H×D)	475mm × 193mm × 620mm (Includes handle and protective bottom corner) 426mm × 177mm × 500mm (Excludes handle and protective bottom corner)		
Weight	<35kg (weight depend on product model and option)		
Power requirements	100 to 120VAC, 50 to 60Hz or 200 to 240VAC, 50 to 60Hz (adaptive power supply)		
Power consumption	< 600W		
Temperature range	Operating temperature range: 0°C to +50°C; Storage temperature range: -40°C to +70°C		

Ordering Information

● Mainframe:

1466C Signal Generator: 6kHz to 13GHz
 1466D Signal Generator: 6kHz to 20GHz
 1466E Signal Generator: 6kHz to 33GHz
 1466G Signal Generator: 6kHz to 45GHz
 1466H Signal Generator: 6kHz to 53GHz
 1466L Signal Generator: 6kHz to 67GHz
 1466N Signal Generator: 6kHz to 90GHz
 1466P Signal Generator: 6kHz to 110GHz

● Standard:

No.	Description	Remarks
1	Power cable assembly	
2	The Product certificate of conformity	/

● Option:

Option No.	Description	Function and performance requirements
Programmable Step Attenuator Option		
1466-H01-130	130dB programmable step attenuator	To expand output power dynamic range for 1466C/D/E/G
1466-H01-90	90dB programmable step attenuator	To expand output power dynamic range for 1466H/L
1466-H01-120	120dB programmable step attenuator	To expand output power dynamic range for 1466H/L
1466-H01-50	50dB programmable step attenuator	To expand output power dynamic range for 1466N/P
1466-H01-B130	Channel B 130dB programmable step attenuator	To expand Channel B output power dynamic range for 1466C/D, Requires option 1466-H11-B13/B20
Low Phase Noise Option		
1466-H04-1	Low phase noise	Improved phase noise performance, 10GHz@10kHz: -120dBc/Hz. For option 1466-H04-1 and 1466-H04-2, one of them must be selected.
1466-H04-2	Ultra low phase noise	Improved phase noise performance, 10GHz@10kHz: -128dBc/Hz. For option 1466-H04-1 and 1466-H04-2, one of them must be selected.
1466-H04-B1	Channel B low phase noise	Improved Channel B phase noise performance, 10GHz@10kHz: -120dBc/Hz, Regarding options 1466-H11-B13/B20, 1466-H04-B1, 1466-H04-B2 either one of them must be selected to configure the 1466 Signal Generator.

Option No.	Description	Function and performance requirements
1466-H04-B2	Channel B ultra low phase noise	Improved Channel B phase noise performance, 10GHz@10kHz:-128dBc/Hz, Regarding options 1466-H11-B13/B20, 1466-H04-2, 1466-H04-B1, 1466-H04-B2, either one of them must be selected to configure the 1466 Signal Generator.
High Power Option		
1466-H05-13	13GHz High output power	Improve maximum output power for 1466C
1466-H05-20	20GHz High output power	Improve maximum output power for 1466D
1466-H05-33	33GHz High output power	Improve maximum output power for 1466E
1466-H05-45	45GHz High output power	Improve maximum output power for 1466G
1466-H05-53	53GHz High output power	Improve maximum output power for 1466H
1466-H05-67	67GHz High output power	Improve maximum output power for 1466L
1466-H05-90	90GHz High output power	Improve maximum output power for 1466N
1466-H05-110	110GHz High output power	Improve maximum output power for 1466P
1466-H05-B13	13GHz Channel B High output power	Improve Channel B maximum output power for 1466C, Option 1466-H11-B13 need to be configured
1466-H05-B20	20GHz Channel B High output power	Improve Channel B maximum output power for 1466D, Option 1466-H11-B20 need to be configured
Dual Channel Option		
1466-H11-B13	13GHz Channel B	Add Channel B, output 6kHz to 13GHz analog signal for 1466C/D
1466-H11-B20	20GHz Channel B	Add Channel B, output 6kHz to 20GHz analog signal for 1466D
Matched Option		
1466-H94	Rack mount kit	Mount kit for rack
1466-H98	English version	
1466-H99	Aluminum alloy transport case	High-intensity portable aluminum alloy transport case, with carrying handle and omni-directional wheel, convenient for transportation
1466-H100	User Manual paper version	A detailed user manual in hard copy is provided.
Analog Modulation Option		
1466-S11	Analog modulation	Add analog modulation function including AM, FM, ΦM
1466-S12	Pulse modulation	Add pulse modulation function, minimum pulse width 100ns
1466-S13	Narrow pulse modulation	Add pulse modulation function, minimum pulse width 20ns

Option No.	Description	Function and performance requirements
1466-S14	LF output/function waveform generator	Add low frequency output and function waveform signal generation
Scanning Option		
1466-S15	Ramp(analog)sweep	Add analog sweep function(Ramp sweep)
1466-S16	Power sweep	Add power sweep function